MO-114D / MO-104D



The overlock sewing machines that create beautiful finished seams.




Lay-in Type Thread Tension Slots

throughout the machine make threading easy and efficient. No wrapping, just follow the color coded thread path.



Lower Looper Threader

allows for easy threading in seconds. Just slide the thread into the slot and snap the looper into place. (MO-114D only)



Cutting Width

can be adjusted quickly for perfect seams

and rolled edges.

MO-114D



Standard Specifications


MO-114D / MO-104D	
Number of Threads	2 / 3 / 4 Threads
Needle	Schmetz 130 / 705H Nm 70, 80, 90
Standard Overlock Width	Left Needle: 5-7mm
	Right Needle: 3-5mm
	Rolled Hem: 1.8-2.2mm
Stitch Length	1-4mm (Standard: 2.5mm)
Differential Feed	0.7-2.0 Ratio
Presser Foot Lift	5mm / 7.5mm
Sewing Speed	Maximum 1,500spm

Other Features

- Adjustable presser foot pressure
- Sewing light
- Upper looper converter (option for MO-104D)

Automatic Rolled Hemming

can be created quickly and easily with built-in fingertip control. There is no need to change the throat plate or foot.





Adjustable Stitch Length

by simply turning dial located on the exterior right hand side within the range of 1 to 4mm. (MO-114D). For MO-104D, the knob is located inside the machine.





Differential Feed

is easily controlled and adjusted by a dial located on the exterior right hand side. (MO-114D). For MO-104D, the dial is located on the exterior left hand side.





Optional Attachments



Blind Stitch Presser Foot




Universal Blind Stitch Presser Foot



Elasticator Presser Foot



Cording Presser Foot



Beading Presser Foot



Curved Beading Presser Foot



Piping Presser Foot



Gathering Presser Foot



